



JABLOTRON NEWS ALERT

March 2008

In this issue:

- *Online image server*
- *JA-68 U.O.M.*
- *Easter Holiday*

Recommended Links:

Jablotron website

Oasis website

Oasis training - dates & details

Nanny website

Image Server for JA-84P

Contact Us:

Jablotron s.r.o.

Pod Skalkou 33
46601 Jablonec nad Nisou
Czech Republic

Sales:

Tel. +420 483 559 945
Tel. +420 483 559 966
Tel. +420 483 559 995
Fax +420 483 559 993
export@jablotron.cz

Technical Support:

Tel. +420 483 559 940
support@jablotron.cz

If you have any comments or wishes regarding *Jablotron News Alert*, please do not hesitate to contact the editor Mr. Mike Williams: williams@jablotron.cz

If your colleagues or friends would like to receive *Jablotron News Alert*, send us their Email addresses to be added to the mailing list.

If you do not wish to receive *Jablotron News* in future, please reply to this e-mail with "Remove" as the subject.



Online Image Server for JA-84P Photos

Images produced and transmitted by the JA-84P wireless PIR camera unit can now be stored and viewed on Jablotron's image server on <http://img.jablotron.cz/>.

Use of this facility is cost-free and is accessible from web browsers at any location with internet connectivity.

Soon after the JA-84P has taken some pictures of intruders, the user can receive an SMS from the control panel on his/her cell-phone (to up to 8 tel. numbers) showing the link to the pictures on the server. If the cell phone is GPRS-enabled then the pictures can be viewed directly, or alternatively from a PC web browser.

The server can even be set to send pictures as attachments in an email, if desired.

Contact the Export Department for price and delivery on the JA-84P PIR camera unit to make your customers' systems stand out from the rest.

JA-68 Universal Output Module

The JA-68 is an optional board for signalling various alarm system events to, for example, an external non-Jablotron communicator, via wired connections. It can be used with JA-6x and JA-8x series systems. The alarm system communicates with the board via its digital bus and it can be installed in the control panel or up to 10 metres away.

Solid-state switch outputs: **Arm, Intruder Alarm, Fire, Tamper, Panic, Technical Fault, AC Failure, and Low Battery.** U+ (12V DC supply) and GND terminals are also supplied.

A relay output is also present which can react to the logical OR function of an installer-configured combination of the above listed alarm events including PGX and PGY activation according to DIP switch settings.

Contact the Export Department for price and delivery.



Easter Holiday

Monday 24th March 2008 is a public holiday in the Czech Republic so Jablotron will be closed for business on this day.

We wish all our readers a happy Easter Season.

