

PSC12010 (DE 06-12) Power supply 12V / 0.5A

This switch-mode power supply is designed for powering a wireless keypad, and also for powering other 12V DC devices like GSM communicators or UC receivers made by Jablotron. The compact dimensions of the case allow installation into a standard electro-installation wall box for hidden installation beneath Jablotron wall-box-mounted products such as the above-mentioned items. The screw holes for M3 screws are also useful for installation in typical fuse/switch boxes where fixing is required.



Installation must always be provided by a qualified electrician.

Technical specifications

Supply voltage	100 ~ 240VAC
Output voltage	12V DC ($\pm 2\%$)
Output current	500 mA
Peak output current T<5 min	1000 mA
Output power	12W max.
Short-circuit protection and overload protection	yes
Casing	IP64
Dimensions	50 x 48 x 25 mm
Input cables, length 300mm (230V)	diameter 1.3 mm (AWG 16)
Output cables, length 300mm (12V)	diameter 0.8 mm (AWG 20)
Operational conditions according to	EN 50131-1 II. Environmental class
Working temperature range	-10°C to +40°C
Complies with	EN 60950-1, EN 61204-3, EN 61000-3-2, 3-3, 6-1, 6-3, EN 55022



PULSAR as the producer hereby declares that the PSC12010 (DE 06-12) is in compliance with the essential requirements and other relevant provisions of Directives 2006/95/EC and 2004/108/EC. The original of the conformity assessment can be found at www.jablotron.com, Technical Support section



Note: Although this product does not contain any harmful materials we suggest you return the product to the dealer or directly to the producer after use.

JABLOTRON
CREATING ALARMS

JABLOTRON ALARMS a.s.
Pod Skalkou 4567/33
46601 Jablonec nad Nisou
Czech Republic
Tel.: +420 483 559 911
Fax: +420 483 559 993
Internet: www.jablotron.cz