

The JA-112J Bus panic or ON/OFF wall button

Technical specifications

Power	from the control panel digital BUS 12 V (9-15 V)
Quiescent current consumption	5 mA
Maximum current consumption	20 mA
Dimensions	80 x 80 x 29 mm
Weight	60 g
Environment	Indoor general
Operation temperature range	-10 °C to + 40 °C
Average operating humidity	75% RH, without condensation
Classification	Security grade 2/Environmental class II (EN 50131-1)
Certification body	Trezor Test s.r.o. (no. 3025)
Complies with	EN 50130-4, EN 55032, EN 50581, EN 50131-1, EN 50131-3, EN 50134-2
Recommended screw	2 x  Ø 3.5 x 40 mm (countersunk head)



JABLOTRON a.s. hereby declares that the JA-112J is in compliance with the relevant European Union harmonisation legislation: Directives No: 2014/30/EU, 2011/65/EU, when used as intended. The original of the conformity assessment can be found at www.jablotron.com – the Downloads section

Note: Disposing of this product correctly will help save valuable resources and prevent any potential negative effects on human health and the environment, which could otherwise arise from inappropriate waste handling. Please return the product to the dealer or contact your local authority for further details of your nearest designated collection point.

The complete version of the manual can be found at:

https://bit.ly/JABLOTRON_JA-112J

JABLOTRON a.s.

Pod Skalkou 4567/33 | 46601 Jablonec n. N.

Czech Republic | www.JABLOTRON.com



UK
CA

JABLOTRON