



## JA-111A Bus external siren

The JA-111A bus external siren is designed to **sound alarms and to signal activation and deactivation of PG outputs** in the security system. The siren communicates with and is powered by the bus.

○ [Declaration of conformity - JA-111A \(PDF 173.22 kB\)](#)

### Description

Also has a power saving function when the power fails and also a built-in spirit level for accurate and easy placement during installation.

Addressable and occupies an alarm system in one position.



**JA-111A-BASE-RB - bottom part with electronics**



**JA-1X1A-C-ST - stainless steel cover**



**JA-1X1A-C-ST-B - stainless steel cover**



**JA-1X1A-C-WH - plastic cover - white**



**JA-1X1A-C-WH-B - plastic cover - white**



**JA-1X1A-C-GR - plastic cover - gray**



**JA-1X1A-C-GR-B - plastic cover - gray**

## Technical specifications

<b>Power</b>	from control panel BUS 12 V (9...15 V)
<b>Current consumption in standby mode</b>	5 mA
<b>Current consumption for cable choice</b>	50 mA
<b>Backup battery</b>	NiCd pack 4.8 V/1800 mAh lifetime approx. 3 years
<b>- minimum loaded voltage</b>	4.0 V
<b>- maximum voltage</b>	6.0 V
<b>reusable battery strap</b>	
<b>Piezoelectric siren</b>	110 dB/m (with fully charged battery)
<b>Dimensions (with cover)</b>	200 x 300 x 70 mm
<b>Classification</b>	Security grade 2
<b>according to</b>	EN 50131-1, EN 50131-4
<b>Environment class IV.</b>	general outdoor -25 °C to +60 °C
<b>Security grade</b>	IP44
<b>Also complies with</b>	EN 50130-4, EN 55022, EN 60950-1, EN 50581

