



CA-2103 GSM/GPS car alarm

GSM/GPS car alarm with support for installation in vehicles with a CAN bus. Besides protection of car entries such as the doors, boot and hood you can extend the installation with up to 24 wireless detectors of the JABLOTRON 100+ series.

o [Declaration of conformity - CA-2103 \(PDF 318,67 kB\)](#)

Kuvas

The car alarm offers partial and full arming and can be controlled by Jablotron remote controls, the original remote controls of the car or both systems. The car alarm offers a Geofence function - information about leaving a defined zone and a departure report (both using SMS). For this product MyJABLOTRON offers the drivers' logbook function with the possibility of identification of up to 99 drivers and a service for displaying the system status and the possibility of its control. The car alarm supports remote FW upgrades.

Tekniset tiedot

Power supply	12/24 V DC (8 - 32V)
Idle current consumption	max. 20 mA
Peak consumption (during communication)	1 A
Working band of the GSM module	E-GSM / GPRS 850/900/1800/1900MHz
Output power of the transmitter	2 W for GSM850/900, 1 W for GSM1800/1900
Operating frequency	868.1MHz
Operating temperature range	-20 °C to +70 °C
SIR output	switching the supply voltage, max. load 1.3 A
Immobilization circuit	8 A permanently, up to 12 A in the short term